


BT50B-1

INDUSTRIAL BRAD NAILER-CT 50MM MAX








BT13 Fastener Summary



Features & Benefits



Accessories

- | | |
|-------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
|  Sequential Trip Trigger
SEQ6 |  Oil Lube
SB32 |
|  Contact Trip Trigger
CNTK2 |  Driver Piston Assembly
101155 |
|  Service Kit
ORK10 | |

Model	BT50B-1	Operating Pressure	PSI	60 - 100
Weight	1.2		BAR	4.2 - 7.0
Dimensions L x W x H (mm)	263 x 230 x 60	Air Consumption Ltr.per shot @ 5.6 bar		0.62
Head (mm)	2 (min) - 2 (max)	Noise	LPA 1sd	76.1
Length (mm)	15 (min) - 50 (max)		LWA 1sd	84.1
Diameter (mm)	1 (min) - 1.25 (max)		LPA 1sd	71.1
Magazine Capacity	100	Vibration m/s2		< 2.5

Stanley Bostitch UK

Gowerton Road
Brackmills Industrial Estate
Northampton NN4 7BW
United Kingdom
+44 (0)870 1 630 630
+44 (0)870 1 670 670

STANLEY

BOSTITCH®