


SB150SLBC-1-E

BOSTITCH CAP STAPLER KIT



SL Fastener Summary



Features & Benefits



Accessories

- Sequential Trip Trigger G1302365
- AI (Adjustable Impulse)
- DIAL-A (Adjustable Depth)
- 360° (360-degree rotation)
- CT (Contact Trip Trigger)
- BC (Bosch Cap Stapler)
- Driver Piston Assembly G0212500
- Contact Trip Trigger G1302700
- Oil Lube SB32

Model	SB150SLBC-1-E	Operating Pressure	PSI	70 - 85
Weight	2.1		BAR	4.8 - 6.2
Dimensions L x W x H (mm)	286 x 270 x 162	Air Consumption Ltr.per shot @ 5.6 bar		1.41
Length (mm)	19 (min) - 38 (max)	Noise	LPA 1sd	83.5
Diameter (mm)	0.9 (min) - 1.3 (max)		LWA 1sd	91.0
Magazine Capacity	150		LPA 1sd	78.0
		Vibration m/s2		3.33

Stanley Bostitch UK

Gowerton Road
Brackmills Industrial Estate
Northampton NN4 7BW
United Kingdom
+44 (0)870 1 630 630
+44 (0)870 1 670 670

STANLEY

BOSTITCH®