

# 416SIC-SJ/16

## SJ/SJK STAPLER-CT 16MM (416)



Diameter: 0.6 - 0.7mm  
 Crown: 4.1 - 4.1mm  
 Length: 4 - 16mm



### Features



Rubber Comfort Grip



Adjustable Exhaust



Contact Trip



Bottom Loading

### SPECIFICATION

|                         |           |           |  |                              |
|-------------------------|-----------|-----------|--|------------------------------|
| Power type              | Pneumatic |           | Shots per charge                       |                              |
| Weight                  | 0.91 kg   |           | Operating pressure                     | 4.00 - 7.00 BAR              |
| Width                   | 44 mm     |           |  | 55.00 - 100.00 PSI           |
| Length                  | 222 mm    |           | Air Consumption Ltr.per shot @ 5.6 bar | 0.24                         |
| Height                  | 156 mm    |           | Air fitting thread type                | 1/4 BSP                      |
| Magazine capacity (max) | 200       |           | Noise                                  | <b>LPA 1sd</b> 78.90         |
| SJK Series Fasteners:   |           |           |  | <b>LWA 1sd</b> 80.30         |
| Diameter (mm)           | 0.6 (min) | 0.7 (max) |  | <b>LPA 1s, 1m</b>            |
| Crown (mm)              | 4.1 (min) | 4.1 (max) | Vibration / Uncertainty                | < 2.5 / N/A m/s <sup>2</sup> |
| Length (mm)             | 4 (min)   | 16 (max)  |  |                              |