

# 450SPIN-AL

## ALU SASH PINNER 50MM MAX



Diameter: 2.4 - 2.8mm  
Length: 25 - 50mm



### Features



Aluminium Housing



Rubber Comfort Grip



Adjustable Exhaust



Contact Trip



Side Loading

### SPECIFICATION

|                            |           |           |  |                            |
|----------------------------|-----------|-----------|--|----------------------------|
| Power type                 | Pneumatic |           | Shots per charge                       |                            |
| Weight                     | 2.54 kg   |           | Operating pressure                     | 4.00 - 7.00 BAR            |
| Width                      | 86 mm     |           |  | 60.00 - 100.00 PSI         |
| Length                     | 368 mm    |           | Air Consumption Ltr.per shot @ 5.6 bar | 2.8                        |
| Height                     | 267 mm    |           | Air fitting thread type                | 1/4 BSP                    |
| Magazine capacity (max)    | 90        |           | Noise                                  | <b>LPA 1sd</b>             |
| SPIN-ALU Series Fasteners: |           |           |  | <b>LWA 1sd</b>             |
| Diameter (mm)              | 2.4 (min) | 2.8 (max) |  | 89.40                      |
| Length (mm)                | 25 (min)  | 50 (max)  |  | <b>LPA 1s, 1m</b>          |
|                            |           |           | Vibration / Uncertainty                | 80.20                      |
|                            |           |           |  | 2.8 / 1.4 m/s <sup>2</sup> |