

5381602

28° BERTA STICK NAILER-ST 160MM MAX



Diameter: 4.2 - 4.6mm
Length: 130 - 160mm



Features



Aluminium Housing



Rubber Comfort Grip



Serrated Tip



Sequential Trip



Auxiliary Handle

SPECIFICATION

| | | | | |
|--------------------------|-----------|-----------|--|-----------------------------|
| Power type | Pneumatic | | Shots per charge | |
| Weight | 7.50 kg | | Operating pressure | 4.50 - 8.30 BAR |
| Width | 140 mm | | | 65.00 - 120.00 PSI |
| Length | 580 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 7 |
| Height | 510 mm | | Air fitting thread type | 3/8 BSP |
| Magazine capacity (max) | 60 | | Noise | LPA 1sd 98.00 |
| BRT 28 Series Fasteners: | | | | LWA 1sd 109.50 |
| Diameter (mm) | 4.2 (min) | 4.6 (max) | | LPA 1s, 1m 96.50 |
| Length (mm) | 130 (min) | 160 (max) | Vibration / Uncertainty | 5.3 / 2.12 m/s ² |
| Head (mm) | 9 (min) | 9 (max) | | |
| Collation type | Plastic | | | |
| Collation angle | 28 | | | |