

541650Q

Q STAPLER-CT 65MM MAX



Diameter: 1.7 - 1.9mm
 Crown: 11.5 - 11.5mm
 Length: 35 - 65mm



Features



Aluminium Housing



Rubber Comfort Grip



Contact Trip



Compact Nose



Easy Jam Clearance

SPECIFICATION

| | | | | |
|-------------------------|------------|------------|--|----------------------------|
| Power type | Pneumatic | | Shots per charge | |
| Weight | 2.20 kg | | Operating pressure | 4.50 - 8.30 BAR |
| Width | 80 mm | | | 65.00 - 120.00 PSI |
| Length | 350 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 1.8 |
| Height | 280 mm | | Air fitting thread type | 1/4 BSP |
| Magazine capacity (max) | 100 | | Noise | LPA 1sd 86.50 |
| Q Series Fasteners: | | | | LWA 1sd 99.00 |
| Diameter (mm) | 1.7 (min) | 1.9 (max) | | LPA 1s, 1m 86.00 |
| Crown (mm) | 11.5 (min) | 11.5 (max) | Vibration / Uncertainty | 3.6 / 1.8 m/s ² |
| Length (mm) | 35 (min) | 65 (max) | | |