

750S4-1

S4/16NC STAPLER-CT 50MM MAX (750)



Diameter: 1.4 - 1.6mm
 Crown: 12.45 - 12.7mm
 Length: 25 - 50mm



Features



Aluminium Housing



Rubber Comfort Grip



Dial-A-Depth



Adjustable Exhaust



Contact Trip



Anti Slip Bumpers



Compact Nose



Jam Free Design

SPECIFICATION

| | | | | |
|-------------------------|-------------|------------|--|------------------------------|
| Power type | Pneumatic | | Operating pressure | 4.20 - 8.40 BAR |
| Weight | 2.41 kg | | | 60.00 - 120.00 PSI |
| Width | 84 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 1.1 |
| Length | 371 mm | | Air fitting thread type | 1/4 BSP |
| Height | 284 mm | | Noise | LPA 1sd 76.50 |
| Magazine capacity (max) | 100 | | | LWA 1sd 84.00 |
| S4 Series Fasteners: | | | | LPA 1s, 1m 71.00 |
| Diameter (mm) | 1.4 (min) | 1.6 (max) | Vibration / Uncertainty | 3.88 / 1.94 m/s ² |
| Crown (mm) | 12.45 (min) | 12.7 (max) | | |
| Length (mm) | 25 (min) | 50 (max) | | |