

F28WW-E  
28° WWELD STICK NAILER-ST +CASE



Diameter: 2.8 - 3.3mm  
Length: 50 - 90mm



Features



Magnesium Housing



Rubber Comfort Grip



Serrated Tip



No-Mar-Tip



Dial-A-Depth



Push Button Depth Control



Sequential Trip



Anti Slip Bumpers



Compact Nose



Carry Case

| SPECIFICATION           |           |           |                                            |                     |
|-------------------------|-----------|-----------|--------------------------------------------|---------------------|
| Power type              | Pneumatic |           | Operating pressure                         | 4.80 - 8.30 BAR     |
| Weight                  | 3.50 kg   |           |                                            | 70.00 - 120.00 PSI  |
| Width                   | 133 mm    |           | Air Consumption Ltr.per shot @ 5.6 bar     | 2.47                |
| Length                  | 508 mm    |           | Air fitting thread type                    | 1/4 BSP             |
| Height                  | 355 mm    |           | Noise                                      | LPA 1sd<br>96.30    |
| Magazine capacity (max) | 90        |           |                                            | LWA 1sd<br>100.10   |
| WW 28 Series Fasteners: |           |           |                                            | LPA 1s, 1m<br>87.10 |
| Diameter (mm)           | 2.8 (min) | 3.3 (max) | Vibration / Uncertainty<br>2.47 / N/A m/s2 |                     |
| Length (mm)             | 50 (min)  | 90 (max)  |                                            |                     |
| Head (mm)               | 7.5 (min) | 7.5 (max) |                                            |                     |
| Collation type          | Wire weld |           |                                            |                     |
| Collation angle         | 28        |           |                                            |                     |