

BT200K-2

KIT BRAD NAILER-ST 50MM MAX



Diameter: 1 - 1.25mm
Length: 15 - 50mm



Features



Magnesium Housing



Rubber Comfort Grip



No-Mar-Tip



Dial-A-Depth



Sequential Trip



Oil Free Engine



Rear Exhaust



Side Loading



Carry Case

SPECIFICATION

| | | | | |
|-------------------------|-----------|------------|--|------------------------------|
| Power type | Pneumatic | | Shots per charge | |
| Weight | 0.95 kg | | Operating pressure | 4.80 - 8.30 BAR |
| Width | 60 mm | | | 70.00 - 120.00 PSI |
| Length | 257 mm | | Air Consumption Ltr.per shot @ 5.6 bar | 0.9 |
| Height | 245 mm | | Air fitting thread type | 1/4 BSP |
| Magazine capacity (max) | 110 | | Noise | LPA 1sd 74.70 |
| BT13 Series Fasteners: | | | | LWA 1sd 79.70 |
| Diameter (mm) | 1 (min) | 1.25 (max) | | LPA 1s, 1m 66.70 |
| Length (mm) | 15 (min) | 50 (max) | Vibration / Uncertainty | 3.68 / 1.84 m/s ² |
| Head (mm) | 2 (min) | 2 (max) | | |