

F33PTSM-E

33° PAPER-TAPE STICK NAILER -ST +CASE













Diameter: 2.5 - 3.3mm
Length: 50 - 90mm



Diameter: 2.5 - 3.3mm
Length: 50 - 90mm



Features

- 
Mg
 Magnesium Housing
- 
 Rubber Comfort Grip
- 
 Serrated Tip
- 
 No-Mar-Tip
- 
DIAL-A
 Dial-A-Depth
- 
 Push Button Depth Control
- 
ST
 Sequential Trip
- 
 Anti Slip Bumpers
- 
 Compact Nose
- 
 Carry Case

SPECIFICATION

Power type	Pneumatic	Operating pressure	4.80 - 8.30 BAR
Weight	3.50 kg		70.00 - 120.00 PSI
Width	133 mm	Air Consumption Ltr.per shot @ 5.6 bar	2.47
Length	360 mm	Air fitting thread type	1/4 BSP
Height	355 mm	Noise	LPA 1sd 90.80
Magazine capacity (max)	50		LWA 1sd 99.70
PT Series Fasteners:			LPA 1s, 1m 86.70
Diameter (mm)	2.5 (min) 3.3 (max)	Vibration / Uncertainty	3.026 / 1.513 m/s ²
Length (mm)	50 (min) 90 (max)		
Head (mm)	6.8 (min) 7.2 (max)		
Collation type	Papertape		
Collation angle	33		
WW 33 Series Fasteners:			
Diameter (mm)	2.5 (min) 3.3 (max)		
Length (mm)	50 (min) 90 (max)		
Collation type	Wire weld		
Collation angle	33		