

F33PTSM-E

33° PAPER-TAPE STICK NAILER -ST +CASE




Diameter: 2.5 - 3.3mm
Length: 50 - 90mm





Diameter: 2.5 - 3.3mm
Length: 50 - 90mm





Features


- 


Magnesium Housing
- 


Rubber Comfort Grip
- 


Serrated Tip
- 


No-Mar-Tip
- 

Dial-A-Depth
- 

Push Button Depth Control
- 

Sequential Trip
- 

Anti Slip Bumpers
- 

Compact Nose
- 

Carry Case

SPECIFICATION

Power type	Pneumatic		Operating pressure	4.80 - 8.30 BAR
Weight	3.50 kg			70.00 - 120.00 PSI
Width	133 mm		Air Consumption Ltr.per shot @ 5.6 bar	2.47
Length	360 mm		Air fitting thread type	1/4 BSP
Height	355 mm		Noise	LPA 1sd 90.80
Magazine capacity (max)	50			LWA 1sd 99.70
PT Series Fasteners:				LPA 1s, 1m 86.70
Diameter (mm)	2.5 (min)	3.3 (max)	Vibration / Uncertainty	3.026 / 1.513 m/s ²
Length (mm)	50 (min)	90 (max)		
Head (mm)	6.8 (min)	7.2 (max)		
Collation type	Papertape			
Collation angle	33			
WW 33 Series Fasteners:				
Diameter (mm)	2.5 (min)	3.3 (max)		
Length (mm)	50 (min)	90 (max)		
Collation type	Wire weld			
Collation angle	33			