

# F33PTSM-E

## 33° PAPER-TAPE STICK NAILER -ST +CASE













Diameter: 2.5 - 3.3mm  
Length: 50 - 90mm



Diameter: 2.5 - 3.3mm  
Length: 50 - 90mm



### Features

-   
**Mg**  
 Magnesium Housing
-   
 Rubber Comfort Grip
-   
 Serrated Tip
-   
 No-Mar-Tip
-   
**DIAL-A**  
 Dial-A-Depth
-   
 Push Button Depth Control
-   
**ST**  
 Sequential Trip
-   
 Anti Slip Bumpers
-   
 Compact Nose
-   
 Carry Case

### SPECIFICATION

Power type	Pneumatic		Operating pressure	4.80 - 8.30 BAR
Weight	3.50 kg			70.00 - 120.00 PSI
Width	133 mm		Air Consumption Ltr.per shot @ 5.6 bar	2.47
Length	360 mm		Air fitting thread type	1/4 BSP
Height	355 mm		Noise	<b>LPA 1sd</b> 90.80
Magazine capacity (max)	50			<b>LWA 1sd</b> 99.70
PT Series Fasteners:				<b>LPA 1s, 1m</b> 86.70
Diameter (mm)	2.5 (min)	3.3 (max)	Vibration / Uncertainty	3.026 / 1.513 m/s <sup>2</sup>
Length (mm)	50 (min)	90 (max)		
Head (mm)	6.8 (min)	7.2 (max)		
Collation type	Papertape			
Collation angle	33			
WW 33 Series Fasteners:				
Diameter (mm)	2.5 (min)	3.3 (max)		
Length (mm)	50 (min)	90 (max)		
Collation type	Wire weld			
Collation angle	33			