

# FN1664-E















## KIT 16GA FINISH NAILER-CT/ST 64MM MAX

**SB16**

Diameter: 1.6 - 1.6mm  
Length: 25 - 64mm



### Features

-  Magnesium Housing
-  Rubber Comfort Grip
-  No-Mar-Tip
-  Dial-A-Depth
-  Anti Slip Bumpers
-  Oil Free Engine
-  Rear Exhaust
-  Compact Nose
-  Rear Loading
-  Carry Case
-  Tool Lock-Out
-  Selectable Trigger
-  Locking Trigger
-  Belt Hook

### SPECIFICATION

Power type	Pneumatic		Operating pressure	4.80 - 8.30 BAR
Weight	1.70 kg			70.00 - 120.00 PSI
Width	86 mm		Air Consumption Ltr.per shot @ 5.6 bar	1.83
Length	302 mm		Air fitting thread type	1/4 BSP
Height	289 mm		Noise	<b>LPA 1sd</b> 85.10
Magazine capacity (max)	110			<b>LWA 1sd</b> 89.20
SB16 Series Fasteners:				<b>LPA 1s, 1m</b> 76.20
Diameter (mm)	1.6 (min)	1.6 (max)	Vibration / Uncertainty	3.1 / 1.55 m/s <sup>2</sup>
Length (mm)	25 (min)	64 (max)		
Head (mm)	3 (min)	3 (max)		
Collation angle	0			