

GF33PT-U

CORDLESS PAPERTAPE FRAMING NAILER



Diameter: 2.5 - 3.3mm
Length: 50 - 90mm



Diameter: 2.5 - 3.3mm
Length: 50 - 90mm



Diameter: 2.5 - 3.3mm
Length: 50 - 90mm



Features



Serrated Tip



Compact Magazine



Carry Case



Tool Lock-Out



Belt Hook



Over-Moulded Grip



Ni-Cd Battery



Fast 60 Min Recharge

SPECIFICATION

Power type	Gas	Charging Time	60 mins
Weight	3.60 kg	Charging Voltage	7.2V
Width	110 mm	Charging Current	1.6A
Length	347 mm	Charger Weight	1.1
Height	353 mm	Battery Weight	0.3
Magazine capacity (max)	55	Battery Type	9B12072R-EU (1.4Ah) Ni-Cd 7.2V
Working ambient temperature	0-40°C	Fuel Cell	80ml
Charger type	9B12073R-U	Noise	LPA 1sd 99.00
Input power source	AC 230V 50Hz		LWA 1sd 108.00
PT Series Fasteners:			LPA 1s, 1m
Diameter (mm)	2.5 (min) 3.3 (max)	Vibration / Uncertainty	3.5 / 1.75 m/s ²
Length (mm)	50 (min) 90 (max)		
Head (mm)	6.8 (min) 7.7 (max)		
Collation type	Papertape		
Collation angle	33		
PT-FC Series Fasteners:			
Diameter (mm)	2.5 (min) 3.3 (max)		
Length (mm)	50 (min) 90 (max)		
Head (mm)	6.8 (min) 7.7 (max)		
Collation type	Papertape		
Collation angle	33		
WW 33 Series Fasteners:			
Diameter (mm)	2.5 (min) 3.3 (max)		
Length (mm)	50 (min) 90 (max)		
Collation type	Wire weld		
Collation angle	33		