

# M10SIC-MG/30

## BRAD NAILER-CT MINI TIP S 30MM MAX



Diameter: 0.8 - 0.8mm  
Length: 15 - 30mm

M10SIC-MG/30 BRAD NAILER-CT MINI TIP S 30MM MAX

### Features



Aluminium Housing



Rubber Comfort Grip



Adjustable Exhaust



Contact Trip



Compact Nose



Bottom Loading

### SPECIFICATION

Power type	Pneumatic		Shots per charge	
Weight	1.02 kg		Operating pressure	4.00 - 7.00 BAR
Width	44 mm			60.00 - 100.00 PSI
Length	235 mm		Air Consumption Ltr.per shot @ 5.6 bar	0.28
Height	180 mm		Air fitting thread type	1/4 BSP
Magazine capacity (max)	180		Noise	<b>LPA 1sd</b> 80.20
MINI S Series Fasteners:				<b>LWA 1sd</b>
Diameter (mm)	0.8 (min)	0.8 (max)		<b>LPA 1s, 1m</b>
Length (mm)	15 (min)	30 (max)	Vibration / Uncertainty	< 2.5 / N/A m/s <sup>2</sup>
Head (mm)	0.8 (min)	1.3 (max)		
Collation angle	0			