

# MIII812CNCT CONCRETE T NAILER-CT



Diameter: 2.5 - 2.5mm  
Length: 19 - 60mm



## Features



Aluminium Housing



Adjustable Exhaust



Contact Trip

## SPECIFICATION

|                         |           |           |  |                               |
|-------------------------|-----------|-----------|--|-------------------------------|
| Power type              | Pneumatic |           | Shots per charge                       |                               |
| Weight                  | 3.23 kg   |           | Operating pressure                     | 4.20 - 7.00 BAR               |
| Width                   | 70 mm     |           |  | 60.00 - 100.00 PSI            |
| Length                  | 275 mm    |           | Air Consumption Ltr.per shot @ 5.6 bar | 2.01                          |
| Height                  | 325 mm    |           | Air fitting thread type                | 3/8 BSP                       |
| Magazine capacity (max) | 66        |           | Noise                                  | <b>LPA 1sd</b> 76.30          |
| T250 Series Fasteners:  |           |           |  | <b>LWA 1sd</b> 82.70          |
| Diameter (mm)           | 2.5 (min) | 2.5 (max) |  | <b>LPA 1s, 1m</b> 69.70       |
| Length (mm)             | 19 (min)  | 60 (max)  | Vibration / Uncertainty                | 3.23 / 1.615 m/s <sup>2</sup> |
| Head (mm)               | 5 (min)   | 5 (max)   |  |                               |
| Collation angle         | 0         |           |  |                               |