

N64084-2-E












COIL NAILER-ST 64MM MAX



Diameter: 2.03 - 2.5mm
Length: 30 - 65mm



Features

-  Aluminium Housing
-  Rubber Comfort Grip
-  Adjustable Exhaust
-  Sequential Trip
-  Steel Frame Protectors
-  Bench Stability
-  Impact Resistant Magazine
-  Compact Nose
-  Twist Magazine
-  Dust & Debris Guard
-  Hanging Port

SPECIFICATION

| | | | |
|-------------------------|---------------------------|--|-------------------------------|
| Power type | Pneumatic | Operating pressure | 4.80 - 8.30 BAR |
| Weight | 2.63 kg | | 70.00 - 120.00 PSI |
| Width | 133 mm | Air Consumption Ltr.per shot @ 5.6 bar | 1.21 |
| Length | 266 mm | Air fitting thread type | 1/4 BSP |
| Height | 327 mm | Noise | LPA 1sd 92.90 |
| Magazine capacity (max) | 350 | | LWA 1sd 98.80 |
| N Series Fasteners: | | | LPA 1s, 1m 85.80 |
| Diameter (mm) | 2.03 (min) 2.5 (max) | Vibration / Uncertainty | 2.75 / 1.375 m/s ² |
| Length (mm) | 30 (min) 65 (max) | | |
| Head (mm) | 4.5 (min) 4.5 (max) | | |
| Collation angle | 15 | | |