

# RN46K-1-E


## ROOFING NAILER-CT 45MM





Diameter: 3.05 - 3.4mm  
Length: 19 - 45mm





### Features


- 


**Mg**  
Magnesium Housing
- 


Rubber Comfort Grip
- 


Dial-A-Depth
- 

Contact Trip
- 

Steel Frame Protectors
- 

Anti Slip Bumpers
- 

Side Loading
- 

Impact Resistant Magazine
- 

Twist Magazine

### SPECIFICATION

Power type	Pneumatic	Operating pressure	4.80 - 7.00 BAR
Weight	2.70 kg		70.00 - 100.00 PSI
Width	117 mm	Air Consumption Ltr.per shot @ 5.6 bar	1.1
Length	277 mm	Air fitting thread type	1/4 BSP
Height	270 mm	Noise	<b>LPA 1sd</b> 76.30
Magazine capacity (max)	120		<b>LWA 1sd</b> 82.70
CR Series Fasteners:			<b>LPA 1s, 1m</b> 69.70
Diameter (mm)	3.05 (min)      3.4 (max)	Vibration / Uncertainty	3.04 / 1.52 m/s <sup>2</sup>
Length (mm)	19 (min)      45 (max)		
Head (mm)	10.1 (min)      10.1 (max)		
Collation angle	15		