

Diameter: 1.6 - 1.6mm Opened size: 19mm Closed size: 4.8 - 8.7mm





## **Features**



Aluminium Housing



Rubber Comfort Grip



Trigger Operated



Air Return Mechanism

| SPECIFICATION             |           |           |                    |                        |                    |
|---------------------------|-----------|-----------|--------------------|------------------------|--------------------|
| Power type                | Pneumatic |           | Operating press    | ure                    | 5.86 - 6.89 BAR    |
| Weight                    | 2.80 kg   |           |                    |                        | 85.00 - 100.00 PSI |
| Width                     | 89 mm     |           | Air Consumption    | Ltr.per shot @ 5.6 bar | 3.3                |
| Length                    | 335.8 mm  |           | Air fitting thread | type                   | 1/4 BSP            |
| Height                    | 188 mm    |           | Noise              | LPA 1sd                | 86.38              |
| Magazine capacity (max)   | 140       |           |                    | LWA 1sd                | 91.47              |
| RING 16 Series Fasteners: |           |           |                    | LPA 1s, 1m             | 78.47              |
| Diameter (mm)             | 1.6 (min) | 1.6 (max) | Vibration / Unce   | rtainty                | < 2.5 / N/A m/s2   |
| Opened size (mm)          | 19        |           |                    |                        |                    |
| Closed size (mm)          | 4.8 (min) | 8.7 (max) |                    |                        |                    |