

SL1838BC-E BOSTITCH CAP STAPLER KIT



Diameter: 0.9 - 1.3mm
Crown: 8 - 8mm
Length: 19 - 38mm



Diameter: 25 - 25mm
Crown: 25 - 25mm



Features



Magnesium Housing



Rubber Comfort Grip



Anti Slip Bumpers



Oil Free Engine



Rear Exhaust

SPECIFICATION

Power type	Pneumatic		Operating pressure	4.80 - 8.30 BAR
Weight	1.77 kg			70.00 - 120.00 PSI
Width	159 mm		Air Consumption Ltr.per shot @ 5.6 bar	1.33
Length	286 mm		Air fitting thread type	1/4 BSP
Height	267 mm		Noise	LPA 1sd 86.59
Magazine capacity (max)	100			LWA 1sd 94.16
SL Series Fasteners:				LPA 1s, 1m 81.20
Diameter (mm)	0.9 (min)	1.3 (max)	Vibration / Uncertainty	2.944 / 1.472 m/s ²
Crown (mm)	8 (min)	8 (max)		
Length (mm)	19 (min)	38 (max)		
SB-CAPS Series Fasteners:				
Diameter (mm)	25 (min)	25 (max)		
Crown (mm)	25 (min)	25 (max)		