

SX1838-E


KIT SX STAPLER-CT/ST 38MM MAX





Diameter: 0.9 - 1.3mm
 Crown: 5.6 - 5.6mm
 Length: 12 - 38mm





Features


- 


Magnesium Housing
- 


Rubber Comfort Grip
- 


No-Mar-Tip
- 


Dial-A-Depth
- 


Anti Slip Bumpers
- 


Oil Free Engine
- 


Rear Exhaust
- 

Compact Nose
- 

Bottom Loading
- 

Carry Case
- 

Tool Lock-Out
- 

Selectable Trigger
- 

Locking Trigger

SPECIFICATION

Power type	Pneumatic		Operating pressure	4.80 - 8.30 BAR
Weight	1.36 kg			70.00 - 120.00 PSI
Width	70 mm		Air Consumption Ltr.per shot @ 5.6 bar	1.33
Length	235 mm		Air fitting thread type	1/4 BSP
Height	240 mm		Noise	LPA 1sd 81.34
Magazine capacity (max)	100			LWA 1sd 87.50
SX Series Fasteners:				LPA 1s, 1m 75.50
Diameter (mm)	0.9 (min)	1.3 (max)	Vibration / Uncertainty	3.06 / 1.53 m/s ²
Crown (mm)	5.6 (min)	5.6 (max)		
Length (mm)	12 (min)	38 (max)		